

871TM 3-wire DC Short Barrel Tubular Sensors



871TM Cable Style
12 mm, 18 mm, and 30 mm Diameter



871TM Mini Quick Disconnect Style
12 mm, 18 mm, and 30 mm Diameter



871TM DC Micro Quick Disconnect Style
12 mm, 18 mm, and 30 mm Diameter

Specifications

Attribute	12 mm, 18 mm, and 30 mm Diameter
Load current	≤ 200 mA
Capacitive load	≤ 1 μF
Leakage current	≤ 10 μA
Operating voltage	10...30V DC
Voltage drop	≤ 1V DC at 200 mA
Repeatability	≤ 10% at constant temperature
Hysteresis	10% typical
Protection type	False pulse, transient noise, reverse polarity, short circuit (trigger at 340 mA typical), overload
Certifications	UL Listed, CSA Certified, CE Marked for all applicable directives, and UKCA Marked for all applicable regulations
Enclosure type rating	NEMA 1, 2, 3, 3R, 4, 4X, 6, 6P, 12, 13 IP67 (IEC529) all models; 1200 psi (8270 kPa) washdown; ToughLink™ and micro connector versions are also rated IP69K (IEC 529)
Housing material	Stainless steel face and threaded barrel
Connection type	• Cable: 2 m (6.5 ft) length, A2 - 3-conductor PVC, C2 - 3-conductor 22 AWG-ToughLink, H2 - 3-conductor 18 AWG ToughLink • Quick disconnect: 4-pin mini style, 4-pin M12 micro style
Status indicators	• Red: Output energized • Green: Power/short circuit (flashing) – 18 mm models only
Operating temperature	-25...+70 °C (-13...+158 °F)
Shock	30 g (1.06 oz), 11 ms
Vibration	55 Hz, 1 mm amplitude, 3 planes

Correction Factors

Target Material	Correction Factors
Steel	1.0
Stainless steel	0.9...1.0
Brass	0.3...0.5
Aluminum	0.1...0.4
Aluminum (≤ 0.02 thick)	0.9...1.1
Copper	0.1...0.2

Product Selection

Barrel Diameter [mm (in.)]	Nominal Sensing Distance [mm (in.)]	Shielded	Output Configuration		Switching Frequency [Hz]	Cat. No.			
						PVC Cable	ToughLink Cable	Mini QD Style	M12 Micro QD Style
12 (0.47)	2 (0.08)	Yes	N.O.	NPN	75	871TM-DH2NN12-A2	871TM-DH2NN12-C2	871TM-DH2NN12-N4	871TM-DH2NN12-D4
				PNP		871TM-DH2NP12-A2	871TM-DH2NP12-C2	871TM-DH2NP12-N4	871TM-DH2NP12-D4
	4 (0.16)	No	N.O.	NPN	70	871TM-DH4NN12-A2	871TM-DH4NN12-C2	871TM-DH4NN12-N4	871TM-DH4NN12-D4
				PNP		871TM-DH4NP12-A2	871TM-DH4NP12-C2	871TM-DH4NP12-N4	871TM-DH4NP12-D4
	2 (0.08)	Yes	N.C.	NPN	75	871TM-DH2CN12-A2	871TM-DH2CN12-C2	871TM-DH2CN12-N4	871TM-DH2CN12-D4
				PNP		871TM-DH2CP12-A2	871TM-DH2CP12-C2	871TM-DH2CP12-N4	871TM-DH2CP12-D4
	4 (0.16)	No	N.C.	NPN	70	871TM-DH4CN12-A2	871TM-DH4CN12-C2	871TM-DH4CN12-N4	871TM-DH4CN12-D4
				PNP		871TM-DH4CP12-A2	871TM-DH4CP12-C2	871TM-DH4CP12-N4	871TM-DH4CP12-D4
18 (0.71)	5 (0.2)	Yes	N.O.	NPN	60	871TM-DH5NN18-A2	871TM-DH5NN18-H2	871TM-DH5NN18-N4	871TM-DH5NN18-D4
				PNP		871TM-DH5NP18-A2	871TM-DH5NP18-H2	871TM-DH5NP18-N4	871TM-DH5NP18-D4
	8 (0.31)	No	N.O.	NPN	40	871TM-DH8NN18-A2	871TM-DH8NN18-H2	871TM-DH8NN18-N4	871TM-DH8NN18-D4
				PNP		871TM-DH8NP18-A2	871TM-DH8NP18-H2	871TM-DH8NP18-N4	871TM-DH8NP18-D4
	5 (0.2)	Yes	N.C.	NPN	60	871TM-DH5CN18-A2	871TM-DH5CN18-H2	871TM-DH5CN18-N4	871TM-DH5CN18-D4
				PNP		871TM-DH5CP18-A2	871TM-DH5CP18-H2	871TM-DH5CP18-N4	871TM-DH5CP18-D4
	8 (0.31)	No	N.C.	NPN	40	871TM-DH8CN18-A2	871TM-DH8CN18-H2	871TM-DH8CN18-N4	871TM-DH8CN18-D4
				PNP		871TM-DH8CP18-A2	871TM-DH8CP18-H2	871TM-DH8CP18-N4	871TM-DH8CP18-D4
30 (1.18)	10 (0.39)	Yes	N.O.	NPN	40	871TM-DH10NN30-A2	871TM-DH10NN30-H2	871TM-DH10NN30-N4	871TM-DH10NN30-D4
				PNP		871TM-DH10NP30-A2	871TM-DH10NP30-H2	871TM-DH10NP30-N4	871TM-DH10NP30-D4
	15 (0.59)	No	N.O.	NPN	30	871TM-DH15NN30-A2	871TM-DH15NN30-H2	871TM-DH15NN30-N4	871TM-DH15NN30-D4
				PNP		871TM-DH15NP30-A2	871TM-DH15NP30-H2	871TM-DH15NP30-N4	871TM-DH15NP30-D4
	10 (0.39)	Yes	N.C.	NPN	40	871TM-DH10CN30-A2	871TM-DH10CN30-H2	871TM-DH10CN30-N4	871TM-DH10CN30-D4
				PNP		871TM-DH10CP30-A2	871TM-DH10CP30-H2	871TM-DH10CP30-N4	871TM-DH10CP30-D4
	15 (0.59)	No	N.C.	NPN	30	871TM-DH15CN30-A2	871TM-DH15CN30-H2	871TM-DH15CN30-N4	871TM-DH15CN30-D4
				PNP		871TM-DH15CP30-A2	871TM-DH15CP30-H2	871TM-DH15CP30-N4	871TM-DH15CP30-D4
Recommended standard QD cordset: -6F = 1.8 m (6 ft), -2 = 2 m (6.5 ft)								889N-F4AFC-6F	889D-F4AC-2